





## 冷压针 Crimp contacts

### 5A 冷压接插针(适用于HM,EMC-008,D-SUB,插芯)

### 5A Crimp contacts (for HM,EMC-008,D-SUB, inserts)

接触电阻  $\leq 3\Omega$  Contact resistance  $\leq 3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CSSM-0.25	61030000178	CSSF-0.25	61030000180
	CSSM-0.33	61030000194	CSSF-0.33	61030000196
	CSSM-0.52	61030000173	CSSF-0.52	61030000174
	CSSM-0.82	61030000182	CSSF-0.82	61030000184
镀金 gold plated	CSGM-0.25	61030000078	CSGF-0.25	61030000080
	CSGM-0.33	61030000094	CSGF-0.33	61030000096
	CSGM-0.52	61030000073	CSGF-0.52	61030000074
	CSGM-0.82	61030000082	CSGF-0.82	61030000084

a	b	c	d	e	f
8.23	4.2	14.0	1.35	1.75	13.6
8.10	4.0	14.8	1.12	1.66	14.4
8.10	4.0	14.8	0.90	1.66	14.4
8.10	4.0	14.8	0.64	1.66	14.4



线规 Wire gauge	剥线长度 Stripping length	
0.09-0.25 mm <sup>2</sup>	AWG 28-24	5 mm
0.13-0.33 mm <sup>2</sup>	AWG 26-22	5 mm
0.33-0.52 mm <sup>2</sup>	AWG 22-20	5 mm
0.33-0.82 mm <sup>2</sup>	AWG 22-18	5 mm

### 10A 冷压接插针(适用于HD,HDD,HM,HK,HQ插芯)

### 10A Crimp contacts (for HD,HDD,HM,HK,HQ inserts)

接触电阻  $\leq 3m\Omega$  Contact resistance  $\leq 3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CDSM-0.37	09150006104	CDSF-0.37	09150006204
	CDSM-0.5	09150006103	CDSF-0.5	09150006203
	CDSM-0.75	09150006105	CDSF-0.75	09150006205
	CDSM-1.0	09150006102	CDSF-1.0	09150006202
	CDSM-1.5	09150006101	CDSF-1.5	09150006201
	CDSM-2.5	09150006106	CDSF-2.5	09150006206
镀金 gold plated	CDGM-0.37	09150006124	CDGF-0.37	09150006224
	CDGM-0.5	09150006123	CDGF-0.5	09150006223
	CDGM-0.75	09150006125	CDGF-0.75	09150006225
	CDGM-1.0	09150006122	CDGF-1.0	09150006222
	CDGM-1.5	09150006121	CDGF-1.5	09150006221
	CDGM-2.5	09150006126	CDGF-2.5	09150006226



线规 Wire gauge	$\phi$	剥线长度 Stripping length	
0.14-0.37 mm <sup>2</sup>	AWG 26-22	0.9	8 mm
0.5 mm <sup>2</sup>	AWG 20	1.1	8 mm
0.75 mm <sup>2</sup>	AWG 18	1.3	8 mm
1 mm <sup>2</sup>	AWG 18	1.45	8 mm
1.5 mm <sup>2</sup>	AWG 16	1.75	8 mm
2.5 mm <sup>2</sup>	AWG 14	2.25	6 mm

### 10A 压簧冷压接插针,带两爪支撑(适用于HD,HDD,HM,HK,HQ插芯)

### 10A take two claws support (for HD,HDD,HM,HK,HQ inserts)

接触电阻  $\leq 3m\Omega$  Contact resistance  $\leq 3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CDSM-0.37B	09150006304	CDSF-0.37B	09150006404
	CDSM-0.5B	09150006303	CDSF-0.5B	09150006403
	CDSM-0.75B	09150006305	CDSF-0.75B	09150006405
	CDSM-1.0B	09150006302	CDSF-1.0B	09150006402
	CDSM-1.5B	09150006301	CDSF-1.5B	09150006401
	CDSM-2.5B	09150006306	CDSF-2.5B	09150006406
镀金 gold plated	CDGM-0.37B	09150006324	CDGF-0.37B	09150006424
	CDGM-0.5B	09150006323	CDGF-0.5B	09150006423
	CDGM-0.75B	09150006325	CDGF-0.75B	09150006425
	CDGM-1.0B	09150006322	CDGF-1.0B	09150006422
	CDGM-1.5B	09150006321	CDGF-1.5B	09150006421
	CDGM-2.5B	09150006326	CDGF-2.5B	09150006426

线规 Wire gauge	$\phi$	剥线长度 Stripping length	
0.14-0.37 mm <sup>2</sup>	AWG 26-22	0.9	8 mm
0.5 mm <sup>2</sup>	AWG 20	1.1	8 mm
0.75 mm <sup>2</sup>	AWG 18	1.3	8 mm
1 mm <sup>2</sup>	AWG 18	1.45	8 mm
1.5 mm <sup>2</sup>	AWG 16	1.75	8 mm
2.5 mm <sup>2</sup>	AWG 14	2.25	6 mm




## 冷压针 Crimp contacts

### 10A 冷压接插针,带三爪支撑(适用于HD,HDD,HM,HK,HQ插芯)

### 10A Crimp contact stake three claws support (for HD,HDD,HM,HK,HQ inserts)

接触电阻  $\leq 3m\Omega$  Contact resistance  $\leq 3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	ZCDSM-0.37	09150006504	ZCDSF-0.37	09150006604
	ZCDSM-0.5	09150006503	ZCDSF-0.5	09150006603
	ZCDSM-0.75	09150006505	ZCDSF-0.75	09150006605
	ZCDSM-1.0	09150006502	ZCDSF-1.0	09150006602
	ZCDSM-1.5	09150006501	ZCDSF-1.5	09150006601
	ZCDSM-2.5	09150006506	ZCDSF-2.5	09150006606
镀金 gold plated	ZCDGM-0.37	09150006524	ZCDGF-0.37	09150006624
	ZCDGM-0.5	09150006523	ZCDGF-0.5	09150006623
	ZCDGM-0.75	09150006525	ZCDGF-0.75	09150006625
	ZCDGM-1.0	09150006522	ZCDGF-1.0	09150006622
	ZCDGM-1.5	09150006521	ZCDGF-1.5	09150006621
	ZCDGM-2.5	09150006526	ZCDGF-2.5	09150006626



M F


线规 Wire gauge	$\Phi$	剥线长度 Stripping length
0.14-0.37 mm <sup>2</sup> AWG 26-22	0.9	8 mm
0.5 mm <sup>2</sup> AWG 20	1.1	8 mm
0.75 mm <sup>2</sup> AWG 18	1.3	8 mm
1 mm <sup>2</sup> AWG 18	1.45	8 mm
1.5 mm <sup>2</sup> AWG 16	1.75	8 mm
2.5 mm <sup>2</sup> AWG 14	2.25	6 mm

### 16A 冷压接插针(适用于HA,HE,HEE,HM,HK插芯)

### 16A Crimp contacts (for HA,HE,HEE,HM,HK inserts)

接触电阻  $\leq 1m\Omega$  Contact resistance  $\leq 1m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CESM-0.37	09330006127	CESF-0.37	09330006227
	CESM-0.5	09330006121	CESF-0.5	09330006220
	CESM-0.75	09330006114	CESF-0.75	09330006214
	CESM-1.0	09330006105	CESF-1.0	09330006205
	CESM-1.5	09330006104	CESF-1.5	09330006204
	CESM-2.5	09330006102	CESF-2.5	09330006202
镀金 gold plated	CESM-3.0	09330006106	CESF-3.0	09330006206
	CESM-4.0	09330006107	CESF-4.0	09330006207
	CEGM-0.37	09330006117	CEGF-0.37	09330006217
	CEGM-0.5	09330006122	CEGF-0.5	09330006222
	CEGM-0.75	09330006115	CEGF-0.75	09330006215
	CEGM-1.0	09330006118	CEGF-1.0	09330006218
镀金 gold plated	CEGM-1.5	09330006116	CEGF-1.5	09330006216
	CEGM-2.5	09330006123	CEGF-2.5	09330006223
	CEGM-4.0	09330006119	CEGF-4.0	09330006221



M F


标示 Identification	线规 Wire gauge	剥线长度 Stripping length
no groove	0.14-0.37 mm <sup>2</sup> AWG 26-22	7.5mm
no groove	0.5 mm <sup>2</sup> AWG 20	7.5mm
1 groove	0.75 mm <sup>2</sup> AWG 18	7.5mm
1 groove	1 mm <sup>2</sup> AWG 18	7.5mm
2 groove	1.5 mm <sup>2</sup> AWG 16	7.5mm
3 groove	2.5 mm <sup>2</sup> AWG 14	7.5mm
wide groove	3 mm <sup>2</sup> AWG 12	7.5mm
no groove	4 mm <sup>2</sup> AWG 12	7.5mm

### 16A 冷压接插针(采用冠簧接触)(适用于HA,HE,HEE,HM,HK)

### 16A Crimp contacts (with crown contact) (for HA,HE,HEE,HM,HK inserts)

接触电阻  $\leq 1m\Omega$  Contact resistance  $\leq 1m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CESM-0.37	09330006327	CESF-0.37G	09330006427
	CESM-0.5	09330006321	CESF-0.5G	09330006420
	CESM-0.75	09330006314	CESF-0.75G	09330006414
	CESM-1.0	09330006305	CESF-1.0G	09330006405
	CESM-1.5	09330006304	CESF-1.5G	09330006404
	CESM-2.5	09330006302	CESF-2.5G	09330006402
镀金 gold plated	CESM-3.0	09330006306	CESF-3.0G	09330006406
	CESM-4.0	09330006307	CESF-4.0G	09330006407
	CEGM-0.37	09330006317	CEGF-0.37G	09330006417
	CEGM-0.5	09330006322	CEGF-0.5G	09330006422
	CEGM-0.75	09330006315	CEGF-0.75G	09330006415
	CEGM-1.0	09330006318	CEGF-1.0G	09330006418
镀金 gold plated	CEGM-1.5	09330006316	CEGF-1.5G	09330006416
	CEGM-2.5	09330006323	CEGF-2.5G	09330006423
	CEGM-4.0	09330006319	CEGF-4.0G	09330006421



M F

标示 Identification	线规 Wire gauge	剥线长度 Stripping length
no groove	0.14-0.37 mm <sup>2</sup> AWG 26-22	7.5mm
no groove	0.5 mm <sup>2</sup> AWG 20	7.5mm
1 groove	0.75 mm <sup>2</sup> AWG 18	7.5mm
1 groove	1 mm <sup>2</sup> AWG 18	7.5mm
2 groove	1.5 mm <sup>2</sup> AWG 16	7.5mm
3 groove	2.5 mm <sup>2</sup> AWG 14	7.5mm
wide groove	3 mm <sup>2</sup> AWG 12	7.5mm
no groove	4 mm <sup>2</sup> AWG 12	7.5mm




## 冷压针 Crimp contacts

### 40A 冷压接插针(适用于HM,HK等插芯)

### 40A Crimp contacts (for HM,HK inserts)

接触电阻  $\leq 0.3m\Omega$  Contact resistance  $\leq 0.3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CCSM-1.5	09320006104	CCSF-1.5	09320006204
	CCSM-2.5	09320006105	CCSF-2.5	09320006205
	CCSM-4.0	09320006107	CCSF-4.0	09320006207
	CCSM-6.0	09320006108	CCSF-6.0	09320006208
	CCSM-10.0	09320006109	CCSF-10.0	09320006209
	镀金 gold plated	CCGM-1.5	09320006304	CCGF-1.5
CCGM-2.5		09320006305	CCGF-2.5	09320006405
CCGM-4.0		09320006307	CCGF-4.0	09320006407
CCGM-6.0		09320006308	CCGF-6.0	09320006408
CCGM-10.0		09320006309	CCGF-10.0	09320006409




线规 Wire gauge	$\Phi$	剥线长度 Stripping length
1.5 mm <sup>2</sup> AWG 16	1.75	9 mm
2.5 mm <sup>2</sup> AWG 14	2.25	9 mm
4 mm <sup>2</sup> AWG 12	2.85	9.6 mm
6 mm <sup>2</sup> AWG 10	3.5	9.6 mm
10 mm <sup>2</sup> AWG 8	4.3	15 mm

### 70A 冷压接插针(适用于HM等插芯)

### 70A Crimp contacts (for HM inserts)

接触电阻  $\leq 0.5m\Omega$  Contact resistance  $\leq 0.5m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CKSM70-10	09320007104	CKSF70-10	09320007204
	CKSM70-16	09320007105	CKSF70-16	09320007205
	CKSM70-25	09320007106	CKSF70-25	09320007206



线规 Wire gauge	$\Phi$	剥线长度 Stripping length
10 mm <sup>2</sup>	4.3	15.5 mm
16 mm <sup>2</sup>	5.5	15.5 mm
25 mm <sup>2</sup>	7	15.5 mm


电缆绞线依据 IEC 60 228-5

### 100A 冷压接插针(采用冠簧接触)(适用于HM,HK插芯)

### 100A Crimp contacts (with crown contact) (for HM,HK inserts)

接触电阻  $\leq 0.3m\Omega$  Contact resistance  $\leq 0.3m\Omega$ 

	公 Male	订货号 Part Number	母 Female	订货号 Part Number
镀银 silver plated	CKSM-10	09110006114	CKSF-10G	09110006214
	CKSM-16	09110006116	CKSF-16G	09110006216
	CKSM-25	09110006125	CKSF-25G	09110006225
	CKSM-35	09110006135	CKSF-35G	09110006235
			开槽结构 Slot structure	
			CKSF-10	09110006414
		CKSF-16	09110006416	
		CKSF-25	09110006425	
		CKSF-35	09110006435	



线规 Wire gauge	$\Phi$	剥线长度 Stripping length
10 mm <sup>2</sup>	4.3	19 mm
16 mm <sup>2</sup>	5.5	19 mm
25 mm <sup>2</sup>	7	19 mm
35 mm <sup>2</sup>	8.2	16 mm

电缆绞线依据 IEC 60 228-5




## 冷压针 Crimp contacts

### 200A 冷压接插针(适用于HM插芯)

### 200A Crimp contacts (for HM inserts)

接触电阻 $\leq 0.3m\Omega$  Contact resistance $\leq 0.3m\Omega$ 镀银  
silver plated

公 Male	订货号 Part Number	母 Female	订货号 Part Number
CHSM200-25	09110006120	CHSF200-25	09110006220
CHSM200-35	09110006121	CHSF200-35	09110006221
CHSM200-50	09110006122	CHSF200-50	09110006222
CHSM200-70	09110006123	CHSF200-70	09110006223



导线截面 Wire gauge	$\Phi$	剥线长度 Stripping length
25 mm <sup>2</sup>	7	22.5 mm
35 mm <sup>2</sup>	8.2	22.5 mm
50 mm <sup>2</sup>	10	22.5 mm
70 mm <sup>2</sup>	11.5	22.5 mm

电缆绞线依据 IEC 60 228-5-

### 保险延迟针

### Relay contact

镀银  
silver plated

线规(mm <sup>2</sup> ) Wire gauge(mm <sup>2</sup> )	型号 Designation	订货号 Part Number
1.0	CESM-1.0R	09330006109
1.5	CESM-1.5R	09330006110
2.5	CESM-2.5R	09330006111

